

Replacement Parts List

NOTE: If requested color is not available, similar color will be substituted.

Part	Cost	Quantity	Total Cost
Buckle Assembly.....	\$6.99	X _____	= \$ _____
Belt Loop (1)*	\$2.00	X _____	= \$ _____
LATCH Belt (1)*	\$4.50	X _____	= \$ _____
Pad Set	\$19.99	X _____	= \$ _____
Locking Clip	\$2.50	X _____	= \$ _____
"S" Clip (1)*	\$2.00	X _____	= \$ _____
Instructions.....	\$0.00	X _____	= \$ _____

*2 are required to use this car bed

Merchandise Total \$ _____

Shipping and handling: \$ _____

Up to \$25.00.....	\$5.95	\$100.01 to \$150.00	\$10.95
\$25.01 to \$50.00	\$6.95	\$150.01 to \$200.00	\$11.95
\$50.01 to \$75.00	\$8.95	\$200.01 and up	\$13.95
\$75.01 to \$100.00	\$9.95	Outside Continental USA	\$10.00

Sales Tax \$ _____

(Arizona, California, Georgia, Indiana, Missouri, South Carolina, and Texas residents add applicable sales tax.)

Grand Total \$ _____

No shipping and handling on instructions for quantities under 6. Add \$.50 for each instruction over 6, then add applicable shipping and handling.

Fill Out For Credit Card
 Visa Mastercard

Card Exp. Date: _____

Cardholder's Name: _____

Card Number: _____

Signature _____

We **MUST** have this information to process your order:

Model Number (8 or 9 characters): _____

Manufacture Date (mm/dd/yyyy): _____

CUT ON DOTTED LINE



4358-6748
4.7.15

Safety 1st

Dream Ride[®] LATCH
Infant Car Bed

5-20 lb (2.3-9 kg) and
26 in. (66 cm) or less

Read all instructions
before using this
car bed.

**KEEP INSTRUCTIONS
FOR FUTURE USE.**



⚠ WARNING:

Failure to follow the warnings on the labels and in the instruction manual can result in serious injury or death to your child.

Table of Contents

 Getting Started	1
Parts of the Car Bed	1
Securing Infant in Car Bed	3
Adjusting Buckle	6
Adjusting Harness Straps	8
 General Use	10
Carrier Use	10
Removing Seat Pad for Cleaning	12
Moving LATCH/Vehicle Belt Loops and LATCH Belts	14
 Safety Information	18
Car Bed Use	18
Vehicle Seating Position	19
Installation in Vehicle	19
 Vehicle Information	20
Understanding Your Vehicle	20
Choosing LATCH or Vehicle Belts	21
Knowing Your Vehicle Belts	22
Aircraft Information	24
Safety Tips	24

 Side Facing	25
 LATCH Installation	26
 Vehicle Belt Installation	29
General Information	31
Using a Locking Clip	31
Dorel Juvenile Group Information	33
Registration and Safety Notices	34
Warranty	35
Replacement Parts Order Form	36

Important Symbols



Vehicle Belts

See pages 22-23 for vehicle belt information.



LATCH

See page 21 for LATCH information and storage location.




To help you recognize instructions which are most critical to your child's safety, we use this symbol.


Failure to follow these warnings can result in the serious injury or death of your child.

Parts of the Car Bed

Front View




- A. Carry Handle
- B. LATCH/Vehicle Belt Loops (2)
- C. LATCH Belt (2)
- D. Foam Inserts
(under seat pad)
- E. Harness Straps
- F. Buckle
- G. Buckle Strap



- H. Buckle Strap Adjustment Slides
(under Car Bed)
- I. LATCH Hooks
- J. LATCH Adjusters

1

Back View




- K. Harness Adjustment Slides
(under pad)
- L. Harness Strap End
- M. Instruction Manual Storage
- N. Locking Clip
(in storage pouch)

2



Securing Infant in Car Bed

Always secure infants on their backs unless your doctor advises you to place the infant on their stomach.



1. Unbuckle Harness

Press in towards the **top** of the red button.

Pull buckle tongues out.


Place harness straps and buckle strap out of the way.




2. Place Infant in Car Bed



3. Position Harness Straps Over Shoulders



4. Pull Buckle Strap Up Between the Legs




5. Buckle Harness

Fit top buckle plate over bottom buckle plate.

Hold buckle tongues with one hand and buckle with the other.

Push buckle tongues into buckle until you hear a "click."



6. Check Harness and Buckle Strap Lengths

The buckle should lay at mid-chest (even with armpits) and away from the infant's neck.

Try to pinch the harness at the shoulders vertically between index finger and thumb as shown.

If your fingers slip off, the harness is tight enough.



If you can pinch the harness strap, you will need to tighten the harness strap.

Adjusting Buckle



Snug harness straps should not allow any slack. They lie in a relatively straight line without sagging. They do not press on the infant's flesh or push the infant's body into an unnatural position.

To adjust the buckle, see pages 6-7.

To adjust the harness straps, see pages 8-9.

⚠ WARNINGS: Failure to fasten and tighten the harness system correctly can result in serious injury or death.



DO NOT put snowsuits or bulky garments on your infant when placing them in the car bed.


Bulky clothing can prevent the harness straps from being tightened properly.

To keep infant warm, buckle your infant in the car bed and place a blanket around the infant or place the infant's coat on backwards after securing infant in the car bed. Make sure blanket or coat does not cover the infant's face in any way. Failure to follow these steps can result in serious injury or death.

To Remove Infant From Car Bed

1. Unbuckle Harness
2. Move Harness Away
3. Remove Infant


5



1. Locate Buckle Strap Adjustment Slides on the Bottom of the Shell



2. Unlace Free End of Buckle Strap from Adjustment Slides



3. To Shorten

Move the adjustment slides closer to shell.

To Lengthen

Move the adjustment slides away from shell.



continued on next page.

6

Adjusting Harness Straps




4. Relace Free End of Buckle Strap Between Slides



5. Pull Buckle Strap Tight So Adjustment Slides Are Flush Against the Shell

⚠ WARNING: Failure to reattach the buckle strap correctly can result in serious injury or death.


7



1. Locate Harness Strap Adjustment Slides Under the Pad



2. Unlace Free End of Harness Strap from Adjustment Slides




3. To Shorten

Move the adjustment slides closer to shell.

To Lengthen

Move the adjustment slides away from shell.




continued on next page.

8




4. Relace Free End of Harness Strap Between Slides




5. Pull Harness Strap Tight So Adjustment Slides Are Flush Against the Shell

⚠ WARNING: Failure to reattach the harness strap correctly can result in serious injury or death.




To Adjust Carrying Handle

Pull handle out from shell on both sides. Rotate up or down to desired location. Make sure both sides of handle are locked before using.



Handle MUST be upright AND locked when carrying and when installed in the vehicle.



Rocker

Rotate the handle all the way back to put the seat in the rocking mode.

Do **NOT** use this position when installed in the vehicle.

Removing Seat Pad for Cleaning



⚠ WARNINGS:

Read ALL instructions before using car bed as a carrier. **NEVER** use carrier unless child is properly secured.

Use only as a carrier by children weighing 5-20 pounds (2.3-9 kg) and 26 inches (66 cm) or less tall.


NEVER leave child unattended. Always keep child within arm's reach.

Suffocation Hazard: Infant carrier can roll over on soft surfaces and suffocate child. **NEVER** place carrier on beds, sofas or other soft surfaces.

Strangulation Hazard: Children have **STRANGLLED** in loose or partially buckled harness straps. Fully restrain the child even when carrier is used outside the vehicle.

Fall Hazard: Child's movement can slide carrier. **NEVER** place carrier near edges of counter tops, tables or other elevated surfaces.

Do not use the carrier if it is damaged or broken, or if any parts are missing.



1. Release Elastic Straps from Plastic Button on Each Side of Shell




2. Pull Pad Off Top of Shell



3. Push Buckle Tongues Through Pad

Moving LATCH/Vehicle Belt Loops and LATCH Belts



4. Pull Pad Off Bottom of Shell

Pull buckle through pad.
Remove pad.

⚠ WARNINGS: Do not use the car bed without the seat pad or foam inserts.

Failure to do this can result in serious injury or death.

Cleaning Pad

Machine wash separately with cold water on a gentle cycle. Do not use bleach. Tumble dry separately for 10-12 minutes on low heat. Remove immediately.

Cleaning Harness Straps, LATCH Belts, LATCH/Vehicle Belt Loops

Spot clean using warm sudsy water and damp cloth.


Replace Pad

Place foam inserts in shell if they have been removed. Starting from bottom of car bed, slip pad on shell. Pull buckle through pad. Pull buckle tongues through pad and wrap pad around top of shell. Make sure harness and buckle straps are not twisted. Reattach elastic to plastic buttons on sides of shell.


If needed, the LATCH/Vehicle belt loops can be moved to either side of the car bed.

Both belt loops must be on the same side as vehicle seat back.


The LATCH belt and LATCH/Vehicle belt loops CANNOT be threaded into the same slots in the shell. When you move the belt loops, you MUST also move the LATCH belts.



1. Pull Corners of Pad Off Shell



2. Lift Metal Clips Up and Pull Belt Loops Out of Slots in Shell



3. Pull "S" Clip and LATCH Strap Out of Slots in Shell




4. Lift up Inside Corner of "S" Clip
Pull clip and LATCH strap away from shell.



5. Unhook LATCH Belt Loop from the "S" Clip
Bunch the LATCH belt to one side as far as possible.




6. Slide Top of Clip Inside the LATCH Belt Loop




7. Pull "S" clip free from LATCH Belt Loop
Repeat steps for other LATCH belt.




8. Pull LATCH Belts Out of Slots



9. Thread LATCH/ Vehicle Belt Loops into Slots



10. Thread LATCH Belts into Slots on Opposite Side of Vehicle Belt Loops



11. Attach "S" clip to LATCH Belt Loop


Insert 2 of the 3 bars on "S" clip into the loop at the end of the LATCH belt.



a. Slide LATCH belt loop across the "S" clip until it bunches up on "S" clip and the top bar of "S" clip is free from the LATCH belt loop.



b. Slide LATCH belt loop back across "S" clip until LATCH belt loop is centered, making sure top and bottom bar is on the outside of the LATCH belt loop.



12. Finished

Make sure all metal clips are flush against the shell.



Store LATCH as shown when not in use.

Do not use this car bed unless the infant is 5-20 lb (2.3-9 kg) and 26 in. (66 cm) or less.

Do not use additional padding in the head area or place blankets near the infant's face. **Watch the infant closely.**

Never take your infant out of the car bed while the vehicle is moving.

Never leave infant unattended.

Placing your infant in a hot car bed may result in burns.

Do not use a car bed with damaged or missing parts.

Do not use cut, frayed or damaged harnesses.

Do not substitute parts or try to modify the car bed in any way.

Do not lubricate buckles and fasteners.

Do not use any car bed accessory except those approved by Dorel Juvenile Group.

Never allow any child to play with this car bed; it is not a toy.

Do not remove or cover up any of the warning labels or other labels on the car bed.

Read all instructions for additional warnings.

On the side of the car bed there is a date of manufacture label. Do not use this car bed more than 8 years after the date of manufacture.



Vehicle Seating Position

Always place this car bed sideways with the infant's head toward the center of the vehicle.

Check the vehicle owner's manual for more information about air bag/car bed use.



Use the car bed only on vehicle seats that face forward.

Do not use on seats that face the sides or rear of the vehicle.



For vehicles without a back seat, refer to your vehicle owner's manual.

If you are not sure where to place the child restraint in your vehicle, consult your vehicle owner's manual, contact Dorel Juvenile Group Consumer Relations Department, or visit your local Child Passenger Inspection Station. Go to <http://www.safercar.gov/cpsApp/cps/index.htm> to find your closest station.

Installation in Vehicle

Check the vehicle belt or LATCH belt before each use. Use only if the belt is tightened properly and securely.


This car bed should be securely belted in the vehicle even when not in use. In a crash or sudden stop, an unsecured car bed could injure occupants.

Do not use a car bed that has been in a crash. You must get a new car bed.

Understanding Your Vehicle



Your vehicle's features may be considerably different than those pictured here.



Consult your vehicle owner's manual to help identify your vehicle's specific features and locations.



Air Bags



LATCH Anchors

Located in the seat bight.




Vehicle Seat Belts



Choosing LATCH or Vehicle Belts

When used correctly the LATCH or Vehicle Belts are equally safe.




LATCH Anchor Bars


The LATCH System

LATCH (Lower Anchors and Tethers for CHildren) is a universal system for installing child restraints without using vehicle seat belts.

The LATCH system can ONLY be used in vehicles that have the LATCH anchor bars installed and designated LATCH seating positions. Most vehicles manufactured after September 2002 are equipped with LATCH. Check your vehicle owner's manual to see which seating positions may be equipped with the LATCH system.



LATCH Hooks



LATCH Storage

To store LATCH on this car bed:

Fully loosen the LATCH belts and pull belts around to the opposite side of the shell and attach the hooks together as shown. Gently pull to remove slack.



Vehicle Belts

If LATCH is not an option, you must use the vehicle seat belt system to install the car bed. There are some vehicle belts that will not work with a car bed or will require special attention. Check your vehicle owner's manual for specific instructions.

⚠ WARNING: Do not use both the LATCH belt and vehicle belt at the same time.

21

Knowing Your Vehicle Belts



Review your vehicle owner's manual for vehicle seat belt use with car beds. This is your best source for information concerning your vehicle.

Not all vehicle belts will work with this car bed. This car bed must be tightly locked in place at all times. You must determine if your vehicle's belts are compatible with this car bed.

Vehicle Belts

• Automatic/Passive vehicle seat belts



You **MUST** have a lap belt to install any car bed. An automatic (passive) shoulder belt may or may not have a separate lap belt.

• Do not use with inflatable seat belts


You may need to move the car bed to another seating location or use LATCH belts only.

• Vehicle belts in center of the door or side panel

You must move the car bed to another seating location.

• Vehicle belts that are in front of the seat bight

You may need to move the car bed to another seating location.



• ELR (Emergency Locking Retractor) vehicle belts

These lap and shoulder belts only lock in a sudden stop or crash, and do not properly secure a car bed alone.

To determine if you have this type of belt, gently pull the belt all the way out of the retractor (spool), let it return several inches, then pull on it again. If it moves freely, it is an ELR belt. If it is locked and will not allow any more belt to come out, it is a switchable retractor.



If you have an ELR lap and shoulder belt, review the "Vehicle Latch Plate" section on page 23 to see if you need a locking clip.

continued on next page.

22



⚠ WARNING: ELR lap-only belts **MUST NOT** be used with this car bed.

• Switchable Retractor

These belts switch from ELR to ALR (Automatic Locking Retractor). You **MUST** have the vehicle belts in the locking mode to use them.

With a switchable retractor, pull the shoulder belt all the way out to switch the retractor into the ALR mode before tightening.

Feed the slack back into the retractor while tightening.

• ALR (Automatic Locking Retractor)


These belts lock after pulling the webbing out and letting the belt go back into the retractor an inch or two.

With an ALR belt, pull the belt all the way out before threading through the car bed.

Vehicle Latch Plates

• Check Latch Plates

Grasp the tongue portion of the latch plate (the part that goes inside the buckle) and pull straight out, in line with the lap belt.



If the latch plate does not slide up and down the vehicle belt, you have a locking latch plate. You should not need to use a locking clip.

If the latch plate slides up and down on the belt, and you have an ELR retractor, you **MUST** use a locking clip to install the car bed. See pages 31-32.

You may not need to use the locking clip with a switchable or ALR retractor.

This car bed is not certified for aircraft use.

Safety Tips:



Children are safer when properly restrained in rear seating positions than in the front seating positions.

According to National Highway Traffic Safety Administration information, children in rear seating positions are statistically safer, whether you have air bags, advanced air bags, or no air bags at all.

To avoid your child being seriously burned, take the following precautions:

1. Park in the shade or where sun does not directly hit the car bed.
2. Cover the car bed with a sheet or blanket when not in use.
3. Check for hot seat and buckles before placing child in car bed.

To help protect your vehicle seat's upholstery from damage, use a single layered towel underneath and behind the car bed.

Side Facing

LATCH Installation




5-20 lb (2.3-9 kg), 26 in. (66 cm) or less, and under 1 year of age.



LATCH Belt



Lap/Shoulder Belt



Lap Belt



⚠ WARNINGS: Failure to place this car bed **side-facing with the child's head toward center of vehicle seat** can result in serious injury or death.

Install side-facing. The back seat is preferred; however, the front passenger seat is acceptable, even with an airbag, as long as the car bed does not interfere with vehicle operation and the passenger seat is moved back as far as possible away from the airbag.

Check vehicle owner's manual for more information about airbag/car bed use.

Safety Tip:

Make sure harness and buckle fit your child correctly before installing the car bed. See pages 3-4.

Review your vehicle owner's manual for LATCH belt use.


⚠ WARNINGS: Do not use LATCH along with the vehicle lap or lap/shoulder belt.

Check LATCH belt before each use. Use only if the belt can be tightened properly and securely.

Failure to follow these warnings can result in serious injury or death.

1. Thread Left LATCH Belt Through Left Belt Loop As Shown

Repeat for right side. Do not twist belt.




continued on next page. 26


2. Place Car Bed Side Facing in the Back Seat with Child's Head Towards the Center of Vehicle Seat

LATCH/Vehicle belt loops must be on the side of the car bed that is against the vehicle seat back as shown.

To move the belt loops and LATCH belts, see pages 14-17.



Handle MUST be upright AND locked when installed in the vehicle.



3. Hook LATCH to Vehicle LATCH Anchor

Fasten one LATCH belt hook to the anchor located in the vehicle seat bight.


Repeat for other side of car bed.



4. Tighten Belt

Lay your forearm across the car bed while pulling up on free end of LATCH belt to tighten.

Repeat for other LATCH belt.



5. Check Belt Tightness

Hold the car bed at the belt path with your weakest hand. Push and pull from side to side.

If it moves more than 1 in. (2.5 cm), try reinstalling the car bed, try another seating location, or try using the vehicle belt.



Vehicle Belt Installation

Safety Tip:


Make sure harness and buckle fit your child correctly before installing the car bed. See pages 3-4.



⚠ WARNINGS: Do not use LATCH along with the vehicle lap or lap/shoulder belt. Store LATCH when using vehicle belts as shown.

Check vehicle belt before each use. Use only if belt can be tightened properly and securely.

Failure to follow these warnings can result in serious injury or death.




Handle MUST be upright AND locked when installed in the vehicle.

1. Place Car Bed Side Facing in the Back Seat with Child's Head Towards the Center of Vehicle Seat

LATCH/Vehicle belt loops must be on the side of the car bed that is against the vehicle seat back as shown.

To move the belt loops and LATCH belts, see pages 14-17.




2. Thread Vehicle Belt

Thread the vehicle lap or lap/shoulder belt combination through belt loops as shown.

Review pages 22-23 and your vehicle owner's manual to determine what kind of vehicle belts you have.

Buckle vehicle belt.



3. Tighten Belt

Lay your forearm across the car bed while pulling up on shoulder belt or free end of lap belt to tighten.



4. Check Belt Tightness

Hold the car bed at the belt path with your weakest hand.

Push and pull from side to side.

If it moves more than 1 in. (2.5 cm), try reinstalling the car bed, try another seating location, or try using the LATCH belts.



Using a Locking Clip

You will rarely need to use a locking clip except in some older vehicles.

Built-in child restraint locking systems have been required in vehicles since 1996, and many vehicles had these features even earlier. Review pages 22-23 and your vehicle owner's manual to determine if your vehicle belts require a locking clip.

A locking clip will not fix all types of seat belt problems. You **MUST** have a lap and shoulder belt to use a locking clip.

For Side Facing installation, follow Pages 29-30 Warnings and Steps 1-3 before starting locking clip installation.



1. Determine Locking Clip Position


Grasp both vehicle belts together just behind the latch plate to mark the position for locking clip. Unbuckle the belt.

NOTE: If the latch plate ends up just at the belt path opening so you cannot grasp the vehicle belt at the latch plate, grasp the vehicle belts on the opposite side of the car bed, as close to the latch plate as possible.




2. Attach Locking Clip

Thread both portions of the vehicle belt onto the locking clip, as close to the latch plate as possible.




3. Position Locking Clip

It should be about 1 in. (2.5 cm) from vehicle belt's latch plate.



4. Rebuckle Vehicle Belt



5. Check Belt Tightness

Hold the car bed at the belt path with your weakest hand.

Push and pull from side to side.

If it moves more than 1 in. (2.5 cm), try reinstalling the car bed or try another seating location.

Remove the locking clip when the seat belt is not being used with a car bed.

Dorel Juvenile Group Information

Thank you for choosing this car bed. The DJG family is committed to creating child restraints with the most comfort and convenience available today.

Remember, parents are a child's first teachers and examples. If you always buckle your seat belt, your child will think it is the natural thing to do. Make it a firm rule that the vehicle does not go until everyone is buckled up. Make no exceptions.

No one can predict if use of a child restraint will prevent injury or death in a particular crash. However, when combined with careful driving, proper use of a child restraint can lower a child's risk of injury or death in most crashes.

Your child's safety is worth the time it will take to read and follow these instructions. After reading, if you still have questions or have any concerns with this car bed, please contact our Consumer Relations Department at:

Website: www.safety1st.djgusa.com

Email: consumer@djgusa.com

Telephone: 1-800-544-1108

M-TH from 8 A.M. to 6 P.M. EST
FRI from 8 A.M. to 4:30 P.M. EST

Mailing Address:

Dorel Juvenile Group, Inc.
Consumer Relations Department
P.O. Box 2609
Columbus, IN 47202-2609

Fax: 1-800-207-8182

Registration and Safety Notices

Please complete the postage-paid registration card that came with your child restraint, and send it to us. Child restraints could be recalled for safety reasons. You must register this restraint to be reached in a recall. Send your name, address, email address if available, and the restraint's model number and manufacturing date to:

Dorel Juvenile Group, Inc.
Consumer Relations Department
PO Box 2609, Columbus, IN 47202-2609


or call 1-800-544-1108 or register online at www.djgusa.com/registration/carseat/us.

For recall information, call the U.S. Government's Vehicle Safety Hotline at 1-888-327-4236 (TTY: 1-800-424-9153), or go to <http://www.NHTSA.gov>.

Consumer: Just fill in your name, address and email. Please print (use dark ink).

Your Name		
Your Street Address		
City		State
E-mail (optional)		
Model Number	Line Code	Manufacture Date
Model Number AB123XXX	Line Code S1 Dream Ride LATCH	Manufacture Date 01/22/2015
L#11 B265035		

Example of model number, manufacture date, and line code.



If you don't have the card or if your address changes, you will find the model number, manufacture date, and line code on the label located on side of shell.

Warranty

Dorel Juvenile Group, Inc. (DJG) warrants this product to the original retail purchaser as follows:

This product is warranted against defective materials or workmanship for one year from the date of original purchase. **An original receipt is required to validate your warranty.** DJG will, at its option, provide replacement parts or replace this product. DJG reserves the right to substitute if the part or model has been discontinued.

To make a claim under this warranty you may email us at consumer@djgusa.com; fax us at 1-800-207-8182 24 hours a day; write to DJG, Consumer Relations Department, P. O. Box 2609, Columbus, IN 47202-2609; or call 1-800-544-1108 from 8:00 a.m. to 6:00 p.m. EST Monday through Thursday and from 8:00 a.m. to 4:30 p.m. on Friday.

Proof of purchase is required and shipping charges are the responsibility of the consumer.

Warranty Limitations: This warranty does not include damages which arise from misuse or abuse of this product.

Limitation of Damages: The warranty and remedies as set forth are exclusive and in lieu of all others, oral or written, expressed or implied. In no event will DJG or the dealer selling this product be liable to you for any damages, including incidental or consequential damages, arising out of the use or inability to use this product.

Limitation of warranties and other warranty terms and state law rights:

Any implied warranties, including implied warranties of the merchantability and fitness for a particular purpose, shall be limited to the duration and terms of the express written warranty. Some states do not allow limitations as to how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you.

This warranty gives you specific legal rights, and you may have other rights, which vary from state to state. Neither DJG nor the dealer selling this product authorized any person to create for it any other warranty, obligation, or liability in connection with this product.

Replacement Parts Order Form

Complete the form. Your model number and manufacturer date code **MUST** be included on the form to ensure proper replacement parts. The codes can be found on a label on side of the child restraint. Payment in U.S. dollars must accompany your order. Choose parts needed from the list on the next page. Return the form with payment to:

Dorel Juvenile Group, Inc.
Consumer Relations Department
P.O. Box 2609
Columbus, IN 47202-2609

Fax orders to: 1-800-207-8182

Please make money orders payable to Dorel Juvenile Group, Inc. Fill in the area on next page to charge to Visa or MasterCard. We do not accept cash or personal checks. All outside of U.S. and Canada **MUST** use credit card.

Ship To: (Please Print)

Name: _____

Address: _____

City: _____

State/Province: _____ **Zip** _____

Telephone: _____

Email Address: _____

We **MUST** have this information:

Model Number (8 to 9 characters): _____

Manufacture Date (mm/dd/yyyy): _____